




Large Sublimation Printer SK-1802H

185cm Width, EPSON I3200A1 Head, High Speed Printer

- Integrated Printhead Lift System – Protects printhead, easy alignment, longer lifespan
- 1.8L Dual-Stage Ink Supply System – Less refilling, continuous printing without interruption
- Front-Mounted Drying System – Fast drying, no smudging
- Dual Motor Rewind – No skewing, no wrinkling, smooth feeding and clean rewinding
- Smart Sensor System – Auto alerts for paper, ink, waste ink, and collision detection

Linko Specification

Model	SK-1802H	
Wide	185 cm 72.83"	
Printhead	Epson I3200 × 2	
Print Resolution & Speed	4Pass: 36 m ² /h (387 ft ² /h) 6Pass: 24 m ² /h (258 ft ² /h) 8pass: 18 m ² /h (194 ft ² /h)	
Ink	Color: CMYK	
	Ink System: 1.8L Bulk Ink Tank + Secondary Ink Cartridges	
Media Type	Sublimation Paper, PP Paper	
Media Feeding	Dual-Motor Feeding & Take-up System	
Drying Mode	External Intelligent Hot Air Integrated Dryer	
Moisturizing System	Fully Sealed Auto Moisturizing & Cleaning	
Optional Features	N/A	
Application Scenarios	Custom production for personalized textiles, gifts, and mass production	
RIP Software	PrintFactory / Photo Print	
Image Format	JPG / TIF / PDF, etc.	
Print Interface	Gigabit Ethernet Port; Laptop users need a Gigabit Ethernet Adapter	
OS Requirements	Windows 10 / Windows 11	
Power Supply	Wide voltage support: AC 110V±10%, 220V±10%, 50–60Hz	
Power Consumption	Printing: 300W; Pre/Post Heating: 800W; Dryer: 1600W	
Operating Temperature	18°C–28°C 64.4°F–82.4°F	
Operating Humidity	50%–60%	
Weight	N.W: 230 kg 507.06 lb N.W: 230 kg 507.06 lb	
Dimensions	Machine: 293 × 80 × 159 cm 115.35" × 31.5" × 62.6"	
	Package: 300 × 149 × 73 cm 118" × 58.66" × 28.74"	

Linko Features



Web: www.dtflinko.com

Email: etro@dtflinko.com

Phone: +86 135 7066 8687 +86 136 3123 0726



Linko Printer



LinkoPrinter



Linko DTF Printer



dtflinko.com

